

Major Specifications of DocuCentre-IV 4070 / 3070

Basic Function/Copy Function		DocuCentre-IV 4070	DocuCentre-IV 3070
Type		Console Type	
Memory ¹⁾		1GB (Max: 2GB)	
HDD ²⁾		160GB (available capacity: 128GB)	
Scanning Resolution		600x600dpi	
Printing Resolution		2,400dpi-equivalentx600dpi	
Half-tone		256 levels	
Warm-up Time		DC model : 19 seconds or less, 19 seconds or less when the main power is on (at room temperature of 20°C) CPF model : 29 seconds or less, 24 seconds or less when the main power is on (at room temperature of 20°C)	
Original Paper Size		Maximum for sheet and book: 297x432 mm (A3, 11x17")	
Output Paper Size	Max.	A3, 11x17"	
	Min.	A5 [For By-pass Tray: Postcards (made by Japan Post Service Co., Ltd.), envelope (235x120mm)]	
	Image Loss	Lead edge 4mm or less, Trail edge 4mm or less, Right & Left Edges 4mm or less	
Output Paper Weight ³⁾	1 Tray	60-105g/m ²	
	2 to 4 Trays	60-216g/m ²	
	By-pass Tray	60-216g/m ²	
First Copy Output Time ⁴⁾		3.1seconds	
Reduction/Enlargement	100%	1:1±0.7%	
	Preset	1:0.500, 1:0.707, 1:0.816, 1:0.866, 1:1.154, 1:1.225, 1:1.414, 1:2.000	
	Variable	1:0.25-1:4.00 (by 1% increments)	
Continuous Copy Speed ⁵⁾	A4LEF/BSLEF	45ppm	35ppm
	A4	32ppm	27ppm
	B4	29ppm	22ppm
	B5	32ppm	27ppm
	A3	24ppm	19ppm
Paper Tray/ Capacity ⁶⁾	Standard	560 sheets x 4 trays + 100 sheets (By-pass Tray)	
	Optional	High-capacity feed tray (one tray): 2,300 sheets	
	Maximum Paper Capacity	4,640 sheets [standard+high-capacity feed tray (one tray)]	
Continuous Copy ⁷⁾		999 sheets	
Output Tray Capacity ⁶⁾⁸⁾		500 sheets (A4LEF)	
Power Supply		AC100V±10%, 15A, 50/60Hz	
Power Consumption		1.5kW or less, Sleep Mode : 2.0W or less, Low Power Mode : 80W or less ⁹⁾ , Standby Mode : 140W or less	
Energy Efficiency		46Wh/h (DC model)	33Wh/h (DC model)
Dimensions	DC/CPF model: (W)640 x (D)685 x (H)1,116mm (with Duplex Automatic Document Feeder)	DC model: (W)640 x (D)685 x (H)1,029mm CPF model: (W)640 x (D)685 x (H)1,116mm (with Duplex Automatic Document Feeder)	
	Machine Weight ¹⁰⁾	DC model: 100 kg (with Duplex Automatic Document Feeder) CPF model: 102 kg (with Duplex Automatic Document Feeder)	DC model: 95 kg CPF model: 102 kg (with Duplex Automatic Document Feeder)
Space Requirement	DC model: (W)971 x (D)1,092 mm (When the Bypass tray is fully extended.) CPF model: (W)989 x (D)685 mm (When the Bypass tray is fully extended, When stopper of DADF is turned on.)		

*1: Additional optional memory may be required depending on functions to be used. Refer to the price list for details. *2: Not all of the indicated hard disk capacity may be available. *3: Use of Fuji Xerox brand paper is recommended. Document may not be printed correctly depending on usage conditions. *4: Figures may change according to machine configurations. *5: The speed may be lower due to image quality adjustment. Productivity made is reduced depending on types of paper and paper trays. *6: Fuji Xerox "P" paper. *7: In order to stabilize the image quality, machine may stop its operation temporarily. *8: When the optional inner catch tray is installed, the capacity of the center tray is 250 sheets (A4LEF), and that of the inner catch tray is 250 sheets (A4LEF). *9: Energy Saver mode is not set in factory default settings. *10: Excluding toner cartridges.

Fax Function (Optional)

Item	Description	
Send Document Size	Max: A3, 11x17", Long size document (Max. 600mm)	
Recording Paper Size	Max: A3, 11x17", Min: A5	
Transmission Time	Less than 2 seconds ¹⁾	
Transmission Mode	ITU-T G3	
Scanning Resolution	Standard	8x3.85 lines/mm, 200x100dpi
	Fine	8x7.7 lines/mm, 200x200dpi
	Super Fine (400dpi)	16x15.4 lines/mm, 400x400dpi
	Super Fine (600dpi)	600x600dpi
Coding Method	MH, MR, MMR, JBIG	
Transmission Speed	G3: 33.6/31.2/28.8/26.4/24.0/21.6/19.2/16.8/14.4/12.0/9.6/7.2/4.8/2.4kbps	
No. of Fax Lines	Telephone subscriber line, PBX, facsimile communication network (PSTN), Max. 3 ports ²⁾ (G3-3 ports)	

*1: When A4 size document with approximately 700 characters is transmitted in standard image-quality (8x3.85 lines/mm) and in high speed mode (28.8kbps or faster, JBIG). Only indicates the time for transmitting the image information and does not include the communication control time. The total communication time will vary depending on the contents of the document, the type of machine receiving the fax, and line condition. *2: Up to three lines can be connected. Number of ports is that of the channels that can be used for communication.

<Reproduction Prohibitions> Please note that reproduction of the following is prohibited by law:

● Domestic and overseas bank notes and coins, government-issued securities, national bonds and local bond certificates. ● Unused postage stamps and post cards. ● Certificate stamps stipulated by law. ● The reproduction of copyrighted works (literary works, musical works, paintings, engravings, maps, cinematographic works, photographic works, etc.) is prohibited except when they are reproduced personally, at home or within limited range.

Print Function (Optional)

Item	Description	
Type	Built-in Type	
Continuous Print Speed ¹⁾	Same as those shown in Fundamental Function/Copy Function	
Print Resolution	Output	600x600dpi, 1,200x1,200dpi
	Data Processing	Standard: 600x600dpi, High resolution: 1,200x1,200dpi
	Standard	ART EX
	Optional	Adobe® PostScript® 3™
Protocol	Ethernet (Standard)	TCP/IP (Ipd, IPP, Port9100, SMB, WSD, Novell® NetWare®, BMLINKS®, ThinPrint®), Novell® NetWare® (IPX/SPX), NetBEUI (SMB), EtherTalk ²⁾
	Parallel (Optional)	Compatible, Nibble, ECP
	Operating System ³⁾	Standard [ART EX Driver] Windows® 2000 Japanese/English, Windows® XP Japanese/English, Windows Server® 2003 Japanese/English, Windows Vista® Japanese/English, Windows Server® 2008 (x86) Japanese/English, Windows® 7 Japanese/English, Windows® XP Professional x64 Edition Japanese/English, Windows Server® 2003 x64 Editions Japanese/English, Windows Vista® 64-bit Japanese/English, Windows Server® 2008 (x64) Japanese/English, Windows Server® 2008 R2 (x64) Japanese/English, Windows® 7 64-bit Japanese/English, [Mac OS X Driver] Mac OS X 10.5-10.7 Japanese/English Optional [Adobe® PostScript® 3™ Kit] Windows® 2000 Japanese/English, Windows® XP Japanese/English, Windows Server® 2003 Japanese/English, Windows Vista® Japanese/English, Windows Server® 2008 (x86) Japanese/English, Windows® 7 Japanese/English, Windows® XP Professional x64 Edition Japanese/English, Windows Server® 2003 x64 Editions Japanese/English, Windows Vista® 64-bit Japanese/English, Windows Server® 2008 (x64) Japanese/English, Windows Server® 2008 R2 (x64) Japanese/English, Mac OS 9.2.2 Japanese/English, Mac OS X 10.3.9-10.4.6/10.4.8-10.4.11/10.5/10.6/10.7 Japanese. *5: When this option is equipped, Ethernet 100BASE-TX/10BASE-T will not be available. *WSD: Web Services on Devices. *XPS: XML Paper Specification. * To print in a Linux® OS environment, please use the Japanese Linux® printer driver which can be downloaded from the Fuji Xerox web site as non-guaranteed software.
Fonts	Standard	Outline (Heisei-Mincho™ W3, Heisei-Kaku-Gothic™ W5, European 19 Fonts), Stroke (Japanese Fonts, European Fonts: for HP-GL)
	Optional	[Adobe® PostScript® 3™ Kit] Heisei 3 Fonts: Japanese 3 Fonts (Heisei-Mincho™ W3, Heisei-Kaku-Gothic™ W5, Heisei-Maru-Gothic™ W4), European 136 Fonts Morisawa 2 Fonts: Japanese 2 Fonts (Ryumin L-KL™, Middle Gothic BBB™), European 136 Fonts [Emulation Kit] European 82 Fonts, Symbol 37 Sets
Emulation	Standard	ART IV, ESC/P (VP-1000), BMLINKS®, PDF, XPS, Docuworks, TIFF, JPEG
	Optional	[Emulation Kit or Adobe® PostScript® 3™ Kit] PC-PR201H, HP-GL (HP7586B), HP-GL2/RTL (HP Design Jet/50C Plus), PCL5/PCL6
Connectivity	Standard	Ethernet 100BASE-TX/10BASE-T, USB2.0 ⁴⁾
	Optional	Ethernet 1000BASE-T ⁵⁾ , Bi-directional parallel (IEEE1284-B)

*1: The speed may be lower due to image quality adjustment. Printing speed may be lower depending on documents when printed in high resolution. *2: The optional Adobe® PostScript® 3™ kit is required. Supports Mac OS 9.2.2 Japanese, Mac OS X 10.3.9/10.4.6/10.4.8/10.4.11/10.5 Japanese. *3: Please refer to the Fuji Xerox web site about the latest compliant OS information. *4: Supports Windows® 2000, Windows® XP, Windows Server® 2003, Windows Vista®, Windows Server® 2008 (x86), Windows® 7, Windows® XP Professional x64 Edition, Windows Server® 2003 x64 Editions, Windows Vista® 64-bit, Windows Server® 2008 (x64), Windows Server® 2008 R2(x64), Windows® 7 64-bit Japanese/English, Mac OS X 10.3.9-10.4.6/10.4.8-10.4.11/10.5/10.6/10.7 Japanese. *5: When this option is equipped, Ethernet 100BASE-TX/10BASE-T will not be available. *WSD: Web Services on Devices. *XPS: XML Paper Specification. * To print in a Linux® OS environment, please use the Japanese Linux® printer driver which can be downloaded from the Fuji Xerox web site as non-guaranteed software.

Scan Function (Optional)

Item	Description	
Type	Color Scanner	
Original Paper Size	Same as those shown in Fundamental Function/Copy Function	
Scanning Resolution	600x600dpi, 400x400dpi, 300x300dpi, 200x200dpi	
Scanning Half-tone	10-bit input, 8-bit output for each RGB color	
Scanning Speed ¹⁾	B&W: 70ipm, Color: 70ipm [Fuji Xerox standard document (A4 LEF), 200 dpi, to device folder.]	
Connectivity	Standard	Ethernet 100BASE-TX/10BASE-T
	Optional	Ethernet 1000BASE-T
Store to Folder	Protocol	TCP/IP (WebDAV, HTTP)
	File Format	B&W Binary: TIFF, DocuWorks ²⁾ , PDF ²⁾ , XPS ²⁾ ; Grayscale: TIFF, JPEG ³⁾ , DocuWorks ²⁾ , PDF ²⁾ , XPS ²⁾ Full Color: TIFF, JPEG, DocuWorks ²⁾ , PDF ²⁾ , XPS ²⁾ ; High-compression DocuWorks ²⁾ , High-compression PDF ²⁾ , High-compression XPS ²⁾
	Driver	TWAIN
Operating System ⁴⁾	Windows® 2000 Japanese/English, Windows® XP Japanese/English, Windows Server® 2003 Japanese/English, Windows Vista® Japanese/English, Windows Server® 2008 (x86) Japanese/English, Windows® 7 Japanese/English, Windows® XP Professional x64 Edition Japanese/English, Windows Server® 2003 x64 Editions Japanese/English, Windows Vista® 64-bit Japanese/English, Windows Server® 2008 (x64) Japanese/English, Windows Server® 2008 R2 (x64) Japanese/English, Windows® 7 64-bit Japanese/English	
	Protocol	TCP/IP (SMB, FTP)
	Operating System	Windows® 2000 Japanese/English, Windows® XP Japanese/English, Windows Server® 2003 Japanese/English, Windows Vista® Japanese/English, Windows Server® 2008 (x86) Japanese/English, Windows® 7 Japanese/English, Windows® XP Professional x64 Edition Japanese/English, Windows Server® 2003 x64 Editions Japanese/English, Windows Vista® 64-bit Japanese/English, Windows Server® 2008 (x64) Japanese/English, Windows Server® 2008 R2 (x64) Japanese/English, Windows® 7 64-bit Japanese/English, Mac OS X 10.2.x/10.3.8/10.3.9/10.4.2/10.4.4/10.4.8/10.4.9/10.4.10/10.5/10.6 Japanese/English, Novell® NetWare® (5.11/5.12) ⁵⁾
File Format	B&W Binary: TIFF, DocuWorks, PDF, XPS, Grayscale/Full Color: TIFF, JPEG, DocuWorks, PDF, XPS, High-compression DocuWorks, High-compression PDF, High-compression XPS, Microsoft® Word documents ⁶⁾ , Microsoft® Excel documents ⁶⁾	
Scan to e-mail	Protocol	TCP/IP (SMTP)
	File Format	B&W Binary: TIFF, DocuWorks, PDF, XPS, Grayscale/Full Color: TIFF, JPEG, DocuWorks, PDF, XPS, High-compression DocuWorks, High-compression PDF, High-compression XPS, Microsoft® Word documents ⁶⁾ , Microsoft® Excel documents ⁶⁾

*1: Scanning speed varies according to the document type. *2: When scanned image is retrieved using CentreWare Internet Services. *3: When Network Scanner Utility 3 is used. *4: Please refer to the Fuji Xerox web site about the latest compliant OS information. *5: Supports only FTP. *6: To use this feature, an optional Advanced Scan Kit is required. The feature is designed to edit / reuse the text/image of the scanned / saved document. This feature is not to guarantee high-quality output result of text, diagrams and pictures on scanned document. *XPS: XML Paper Specification.

* If the storage media (hard disk) of the product fails, the data received, stored, or registered in the media may be erased. Fuji Xerox will not be held responsible for any damage caused due to such loss of data.
* Key repair components will be available for at least 7 years after the product is no longer manufactured.

<For Your Safe Use>
● Before using the product, read the Instruction Manual carefully for proper use. ● Use the product with an appropriate and adequate power source and voltage displayed. ● Be sure to ground the machine. In the case of a failure or short circuit, an electric shock may result.



For comments about Fuji Xerox and consultation, contact the **Customer Information Center.**

0120-27-4100

Toll-free call service time: 9:00 to 12:00 and 13:00 to 17:00 excluding Saturdays, Sundays and national holidays (at Headquarters in Tokyo). However, you cannot use this service with an extension telephone with call area restrictions. Please use a nation-wide call available telephone.

The telephone call might be recorded to correctly understand your inquiry or to later check how the receiver provided support.

DocuCentre-IV

4070 / 3070



DocuCentre-IV 4070 / 3070

Digital Black and White Multifunction Device



New Product Topics

The DocuCentre-IV 4070/3070 black and white multifunction device, offering "Easiness" to your real-life work



Digital Black and White Multifunction Device

DocuCentre-IV 4070/3070

Copy	Print	Fax	Scan
B&W 45 ppm*1	B&W 45 ppm*1	Super G3 Compatible	Color / B&W 70 ppm*2

*1: When using A4 LEF, DocuCentre-IV 4070. 35 ppm when using DocuCentre-IV 3070.
*2: Fuji Xerox standard document (A4 LEF), 200 dpi, to device folder.

DocuCentre-IV 4070/3070	Copy	Print	Fax	Scan	Duplex Automatic Document Feeder
3070 DC model	●	○	○	○	○
4070 DC model	●	○	○	○	○
4070/3070 CPF model	●	●	●	○	●

※ The photo is of the DocuCentre-IV 4070 CPF model.

● Standard ○ Optional

We propose a more convenient use of information by linking mobile devices with Working Folders.

Mobile & Cloud Service Linkage

From your smartphone outside of the office:

- Viewing, registering, downloading documents.



From a MFD:

- Download printing
- Automatic registration of received fax documents
- Scan registering



From the web browser or DocuWork Desk of your PC:

- Administrator function, searching, drag & drop

Documents can be viewed when you are away from the office using smartphones and tablet devices. Even if you do not have a document server at your company, a Working Folder can be used to enable smooth digitization and information sharing without being restricted to a specific location.

Waste-free powering only the parts that are used!



Smart Energy Management Technology

The device has reduced power consumption and CO₂ emissions by dividing the device into four modules; "scanner," "control panel," "output device," and "controller," and only activating the parts that are to be used for a current function. In addition, users close the device are not bothered by noises for jobs that do not use the document feeding and output device.

Paper documents immediately converted to editable data!



Conversion to Word / Excel®

Not only can texts be extracted from scanned images, combined tables with texts and design patterns can also be recognized and directly converted to editable Microsoft® Word and Excel® document formats. When your document is in paper or even when your digital data lost, these documents can be easily re-generated.

※ Optional. HDD Extension Kit, Extension System Memory (1GB), Scanner Kit, Advanced Scan Kit are required.

Control panel usable in approximately 3 seconds

High-speed reactivation of control panel

Previously when a device is recovering from the sleep mode, the control panel to be displayed after waiting for the output device to warm up. For the DocuCentre-IV 4070 model series, the control panel is operational in approximately 3 seconds after pressing the energy saver button. Therefore, the user can perform operations without waiting for the device to become operational.



Scanned data to USB flash memory

Scan to USB

If you insert your USB flash-memory to the socket on the control panel, a pop-up will show the functions you can use with it. You can smoothly store scanned data and print stored documents to and from the USB flash-memory.

※ Optional. HDD Extension Kit, Extension System Memory (1GB) and Scanner Kit are required.



A cloud service that directly links with multifunction devices!



Working Folder

Fuji Xerox's "Working Folder" cloud service can be linked and directly accessed from a multifunction device. Scanned documents and received fax documents can be forwarded and stored documents can be outputted. Documents in the cloud can be operated using DocuWorks Desk, and can also be viewed and operated from smartphones.

※ The conclusion of the Working Folder Service contract is required in using this function.

※ Optional. HDD Extension Kit, Extension System Memory (1GB), Printer Kit, Scanner Kit, Fax Kit2 are required.

Outputting from multifunction device with a tablet device

Print Utility for iOS / Android™

A dedicated printing application that supports the iPhone, iPad, and Android™ devices is provided free-of-charge. This enables you to print Web pages, photos, address book contacts*, and captured images, etc. via a wireless LAN access point.

※ Print Utility for iOS can be downloaded from the App Store free-of-charge, and Print Utility for Android™ can be downloaded from the Android™ Market free-of-charge.

※ Printer kit is required.

* Print Utility for iOS only.

